



Model: 10HD7

10 Inch Monitor

This 10 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 10 inch monitor has a lightweight housing and is ideal for desktop and wall mounting. The 10HD7 can be connected via HDMI, VGA, BNC or RCA connections.

- 1920 x 1200 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- Mounting: Wall, desktop
- External dimensions: 9.6 x 6.7 x 1.3 inches











© 2024 Beetronics



Phone: 647-557-7931 E-mail: info@beetronics.ca Web: www.beetronics.ca



General

Manufacturer	Beetronics
Item number	10HD7
Previous model	10HD6
Product name	10 Inch Monitor
Warranty	2 years
User Manual	Download PDF
Quickstart	Download PDF

Panel

Diagonal size	10.0 inches (254 mm)
Panel type	IPS-LCD
Aspect ratio	16:10 (16:9, 4:3 adjustable)
Response time	10 ms
MTBF	50K
Native resolution	1920 x 1200
Supported resolutions	1920 x 1200 (max), 640 x 480 (min)
Pixels per inch	224 PPI
Backlight	LED
Brightness	300 cd/m2
Contrast	1500:1
Viewing angle	178° horizontal, 178° vertical



Unit 7 #204 Brampton, ON L6T 0E9 Canada

© 2024 Beetronics

E-mail: info@beetronics.ca Web: www.beetronics.ca

2



Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
AUX input	1x
AUX output	1x
USB-A	1x integrated USB media player

Size & weight

Colour	Black
Weight	1.1 lbs (2.0 lbs with stand)
Width	9.5 inches
Height	6.7 inches
Thickness	1.3 inches
Display dimensions	8.5 x 5.3 inches

Features and functions

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically
Orientation	Landscape, portrait, face-up
USB media player	The monitor is equipped with a built-in USB media player.



Phone: 647-557-7931 E-mail: info@beetronics.ca Web: www.beetronics.ca



Power

Input voltage	DC 9-33V
Consumption	5.5 Watt
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 12V-2A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

Environmental

Max. non-stop operating time	24/7
Operating temperature	-4°F to +140°F
Storage temperature	-4°F to +158°F
Operating humidity	20% - 80% non-condensing

Mounting

Wall mount	
Flush mount	
Stand	Adjustable and detachable

Certifications & Standards

Certifications	CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, CCC

Package content

Includes	Monitor, Manual, Remote control, AC power adapter, Stand

© 2024 Beetronics



Phone: 647-557-7931
#204
E-mail: info@beetronics.ca
tton, ON L6T 0E9
Web: www.beetronics.ca



Compatible accessories

Rack mounting	Compatible with 19 inch rack mount kit (RMK2)
Wall mounting	Compatible with flat wall mount bracket (VWB1)
Stand	VDK3 included as standard



© 2024 Beetronics



Phone: 647-557-7931

Web:

E-mail: info@beetronics.ca

www.beetronics.ca

